













Connection Cable S4 with female angled plug

Designation	Connection Cable S4/3		Connection Cable S4/4		Connection Cable S4/5	
Application	3-pole female, with moulded cable, for units with plug S4		4-pole female, with moulded cable, for units with plug S4		5-pole female, with moulded cable, for units with plug S4	
						
						
Design	Moulded cable		Moulded cable		Moulded cable	
Cable material	PVC		PVC		PVC	
Wire diameter	3 x 0,25 mm ²		4 x 0,25 mm ²		5 x 0,25 mm ²	
Protection class	IP 67/68		IP 67/68		IP 67/68	
Ambient temperature	-25 ... +80 °C		-25 ... +80 °C		-25 ... +80 °C	
	Type	Art.-No.	Type	Art.-No.	Type	Art.-No.
Cable length of 2 m	ST041/3-2	9850F	ST041/4-2	9841D		
Cable length of 5 m	ST041/3-5	9841R	ST041/4-5	9841E	ST041/5-5	9841Q
Cable length of 10 m			ST041/4-10	9841S	ST041/5-10	9850H
Cable length of 15 m			ST041/4-15	9842O		

Designation	Connection Cable S4/3 PUR		Connection Cable S4/4 PUR		Connection Cable S4/4 H	
Application	3-pole female, with moulded cable, for units with plug S4		4-pole female, with moulded cable, for units with plug S4		4-pole female, with moulded cable, for units with plug S4	
						
						
Design	Moulded cable		Moulded cable		Moulded cable	
Cable material	PUR		PUR		PP	
Wire diameter	3 x 0,25 mm ²		4 x 0,25 mm ²		4 x 0,34 mm ²	
Protection class	IP 67/68		IP 67/68		IP 69K	
Ambient temperature	-25 ... +80 °C		-25 ... +80 °C		-30 ... +105 °C	
	Type	Art.-No.	Type	Art.-No.	Type	Art.-No.
Cable length of 2 m			ST041/4-2 PUR	9850F		
Cable length of 5 m	ST041/3-5 PUR	9850B	ST041/4-5 PUR	9850G	ST041/4-5H	9842M
Cable length of 10 m			ST041/4-10 PUR	9850E	ST041/4-10H	9844N
Cable length of 15 m					ST041/4-15H	9842N
Cable length of 20 m	ST041/3-20 PUR	9850M				